

Swayway - Midi Chimes

Mauricio Melo
New York University
23 Old Mamaroneck Rd. apt. 4S
White Plains, NY 10605
914 831 3179
mm1751@nyu.edu

Doria Fan
New York University
101 Lafayette Ave. Apt. 7F
Brooklyn, NY 11217
718 935 9270
doria@nyu.edu




Figure 1. Swayway

ABSTRACT

The Swayway is an audio/MIDI device inspired by the simple concept of the wind chime.

This interactive sculpture translates its swaying motion, triggered by the user, into sound and light. Additionally, the motion of the reeds contributes to the visual aspect of the piece, converting the whole into a sensory and engaging experience.

Keywords

Interactive sound sculpture, flex sensors, midi chimes, LEDs, sound installation.

1. INTRODUCTION

This project is inspired by the simple concept of the wind

Permission to make digital or hard copies of all or part of this work for personal or classroom use is granted without fee provided that copies are not made or distributed for profit or commercial advantage and that copies bear this notice and the full citation on the first page. To copy otherwise, or republish, to post on servers or to redistribute to lists, requires prior specific permission and/or a fee.

NIME'05, May 26-28, 2005, Vancouver, BC, Canada.

Copyright remains with the author(s).

chimes. For centuries bells have been generally associated to the most varied meanings according to cultures, traditions and rites. The idea was to represent this very simple wind chimes concept trying to keep the simplicity of the object, while adding interaction. The swaying motion of the reeds, also recall the typical swinging movement of the wind chimes but inverted; that is from the base up, as opposed to the hanging motion of the bells.

2. HOW IT WORKS

A microphone captures the ambient sound around the piece. Using MaxMSP, the audio is decomposed into basic harmonics. These frequencies are converted into MIDI signals, and outputted as MIDI sounds. Flexible sensors attached to the plastic reeds and connected to microcontrollers sense the bending movement, translating it into a signal that modifies the pitch of the previously processed audio signals. At the same time, these signals activate a set of LEDs that also reflect the reed's movements – the greater the movement, the brighter the LEDs.




Figure 2. Signal Flow Diagram

A separate smaller control device allows the user to modify the tempo and select predefined sound combinations through two potentiometers. The flex-sensors are wired to two PIC microcontrollers. One processes the movement information and sends out one MIDI continuous control message to

MaxMSP, while the other PIC takes care of the 24 LEDs mounted on the wooden base.

The two potentiometers mounted on a separate controller, also send values to one of the PIC microcontroller which sends out two MIDI continuous control messages to MaxMSP allowing sound sets and tempo to be modified by the user.

3. INTERACTION

User stands in front of the device. With one or both hands starts to touch, bend and play with the reeds. This causes pitch of the outgoing sounds to change according to movements. LEDs also reflect the reeds movements -the greater the movement, the brighter the LEDs



Figure 3. User interaction

4. INTERFACE

This audio MIDI device is built of a square wooden bed from where 17 plastic reeds emerge to tips capped in similarly light wood. Flex-sensors at the base of 7 reeds detect the bending motion, modifying the audio output. Simultaneously, 24 Green LEDs nested at the foot of the reeds respond to the bending action. A separate control device that allows the user to modify parameters is also built of wood with two potentiometers.




Figure 4. Controller with two Potentiometers

5. CONCLUSION

As a result of this experience, we have now an interesting device for future testing. It's clear that this is not, and does not pretend to be a musical instrument. It's a tool with which to explore the sensory aspect of sound. Flex-sensors used for this piece are still pretty temperamental and uneven y their readings. Probably with more precise sensors better results could be achieved. Also MIDI sounds could be improved or perhaps recorded and processed in real time as audio signals.

6. ACKNOWLEDGMENTS

Our thanks to Jeff Feddersen, our Physical Computing instructor and to Daniel Palkovski for their help in this project.

7. REFERENCES

- [1] Truman, D., Cook, P. *Bossa: The Deconstructed Violin reconstructed*, Journal of New Music Research, June 2000, vol. 29 no. 2, pp. 121-130
- [2] Bahn, C., Hahn, T.,. *Pikapika- The collaborative Composition of an Interactive Sonic Character*, Dissertation on music composition. Princeton University, 2001.
- [3] Huber, D. *The MIDI Manual, A practical guide to MIDI in the project studio* Elsevier Science, Burlington, MA, 1999.
- [4] Igoe, T., O'Sullivan D. *Physical Computing. Sensing and Controlling the Physical World with Computers* Thomson Course Technology, NY, 2004.